

Bitzer 6F.2 (x3)

Specifications

Merk	Bitzer
Type	6F.2 (x3)
Koudemiddel	Freon
kW at +10°C/+40°C	497,7*
kW at 0°C/+40°C	382
kW at -5°C/+40°C	317,1
kW at -10°C/+40°C	260,9
kW at -20°C/+40°C	170
kW at -30°C/+40°C	103,2
kW at -40°C/+40°C	55,5
Elektromotor Specs	37
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
Vloeistof tank	✓
Vloeistof tank ltr.	30
Olie afscheider	✓
Filter droger	✓
Kijk glas	✓
Schakelkast	✓
Opmerkingen	# // *Capacity based on +7,5C/+40C // Electromotor: 37 kW at 1475 RPM // DX Unit



Opmerkingen	R404a - R22 or other freon types
Package / Rack	✓
Afmetingen	2900x1500x1750 mm (LxWxH)
Stock	1

Description

Used Bitzer 6F.2 (x3)

Gebruikt Bitzer 6F.2 (x3) freon compressorrek, compleet met onbelaste start, capaciteitsregeling, drukveiligheidsschakelaars, manometers, olieafscheider, vloeistofleiding filterdroger, kijkglas, bedieningspaneel en vloeistofvat met een inhoud van 30 liter.









