

Sabroe SMC 108 L MK2 cool/freeze unit

Specifications

Merk	Sabroe
Type	SMC 108 L MK2 cool/freeze unit
Koudemiddel	Freon
Refrigerant type	R22
kW at 0°C/+40°C	391
kW at -10°C/+40°C	255
kW at -40°C/+40°C	71
Elektromotor Specs	N/A
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
m3 / h	438
Opmerkingen	255kW at *10°C/+35°C // 71kW at -40°C/-10°C at 1500 RPM
Stock	1



Description

Used Sabroe SMC 108 L MK2 cool/freeze unit

Gebruikte V-riem aangedreven Sabroe SMC 108 L zuigercompressor met Electromoto. Onze capaciteitstabel is gebaseerd op NH3. Voor alle andere specificaties (indien beschikbaar), zie de afbeelding van het typeplaatje van de fabrikant of het bijgevoegde pdf-bestand. * Waarom kiezen voor HOSBV? We waren niet alleen de grootste specialist in gebruikte koeling in Europa, maar we leveren ook alle apparatuur, inclusief een uitgebreide test, garantie en industriële reiniging. * Optioneel kunnen we ook een nieuwe verfbeurt uitvoeren en de logistiek regelen.



Model	Number of cylinders	Swept volume at 1500 rpm	Swept volume at 1800 rpm	R717 *						Unit dimensions in mm			Weight excluding motor	Sound pressure level at 1500 rpm	Sound pressure level at 1800 rpm
				Nominal capacities in kW at 1500 rpm		Nominal capacities in kW at 1800 rpm				L	W	H			
				Single-stage	Booster	Single-stage	Booster	Single-stage	Booster						
				-10/-15°C	0/+40°C	-10/-15°C	0/+40°C	-10/-15°C	0/+40°C				kg	dB(A)	dB(A)
SMC 104 S	4	226	271	127	195	35	53	235	42	2261-2865	1213	1229	1195	79	82
SMC 104 L	4	263	339	165	250	47	198	300	57	2261-2865	1213	1229	1215	80	83
SMC 104 E	4	339	N/A	203	306	58	N/A	N/A	N/A	2261-2865	1213	1229	1220	80	83
SMC 106 S	6	339	407	191	293	53	229	352	64	2286-2890	1267	1247	1380	81	83
SMC 106 L	6	424	539	247	375	71	297	490	85	2286-2890	1267	1247	1400	82	84
SMC 106 E	6	509	N/A	304	459	87	N/A	N/A	N/A	2286-2890	1267	1247	1400	82	84
SMC 108 S	6	462	541	255	391	71	300	489	85	2312-2915	1261	1247	1395	82	84
SMC 108 L	8	566	679	330	500	94	396	600	113	2312-2915	1261	1247	1630	83	85
SMC 108 E	8	679	N/A	406	612	116	N/A	N/A	N/A	2312-2915	1261	1247	1650	83	85
SMC 112 S	12	679	814	382	586	106	419	703	137	3279-3887	1475	1448	2255	85	85
SMC 112 L	12	846	1028	465	750	141	593	900	169	3279-3887	1475	1448	2280	85	86
SMC 112 E	12	1038	N/A	609	918	175	N/A	N/A	N/A	3279-3887	1475	1448	2330	85	86
SMC 116 S	16	905	1086	520	782	141	612	938	170	3329-3937	1536	1445	2505	84	86
SMC 116 L	16	1135	1387	619	1000	188	791	1200	226	3329-3937	1536	1445	2535	84	87
SMC 116 E	16	1357	N/A	812	1214	231	N/A	N/A	N/A	3329-3937	1536	1445	2590	84	87