

Sabroe SAB 128 HF mk2 (x2) package

Specifications

Merk	Sabroe
Type	SAB 128 HF mk2 (x2) package
Koudemiddel	NH 3 / Freon
kW at -10°C/+40°C	176.4
kW at -20°C/+40°C	283
Elektromotor Specs	37 kW at 2935 RPM
Op stalen frame	✓
Vloeistof tank	✓
Olie afscheider	✓
Opmerkingen	Capacity based on -40°C/-10°C / -30°C/-5°C // Electromotor: 37 kW at 2935 RPM // Booster Compressors // Can also be used as Freon set / 212,2 at -40°C/-10°C / 319 at -30°C/-5°C
Package / Rack	✓
Stock	1



Description

Used Sabroe SAB 128 HF mk2 (x2) package

Gebruikt Sabroe SAB 128HF schroefcompressor skid. Zie voor alle andere specificaties de afbeelding van het typeplaatje van de fabrikant of het bijgevoegde pdf-bestand (indien beschikbaar). * Waarom kiezen voor HOSBV? We waren niet alleen de grootste specialist in gebruikte koeling in Europa, maar we leveren ook alle apparatuur, inclusief een uitgebreide test, garantie en industriële reiniging. * Optioneel kunnen we ook een nieuwe verfbeurt uitvoeren en de logistiek regelen.




SAB 128 screw compressor block with balanced overflow valve type POV

Cooling capacities * kW at 2960 rpm									
Model	R717		R22		R404A		With economiser		
	High stage	Booster	High stage	High stage	High stage	R717	R22	R404A	
SAB 128 HM	187.9	58.9	178.4	240.5	183.9	245.4	50.3	64.7	73.5
SAB 128 HF	294.9	92.5	280.0	379.4	288.6	385.2	78.9	101.0	113.9

* 5 °K liquid sub-cooling / 5 °K suction superheat for R717 / 15 °K suction superheat for R404A and R22

Technical data						
Model	Swept volume ⁽¹⁾		Length ⁽²⁾	Width ⁽²⁾	Height ⁽²⁾	Weight ⁽³⁾
	2950 rpm	3550 rpm				
SAB 128 HM	303 m ³ /h	364 m ³ /h	2200 mm	1420 mm	1405 mm	1150 kg
SAB 128 HF	454 m ³ /h	547 m ³ /h	2200 mm	1420 mm	1405 mm	1150 kg

(1) Drive motor speed – (2) With refrigerant-cooled oil cooler – (3) Excluding electric motor – (4) Free field – one metre distance

All data are subject to change without notice

SAB 0009