

Goedhart DVS 61457

Specifications

Merk	Goedhart
Type	DVS 61457
Capaciteit kW	7,5
Koudemiddel	Freon
Aantal Ventilatoren	1
Lamel afstand in mm	7
Ontdooiing	None
Dubbel blazend	✓
m ³ /h	4915
Afmetingen	1040x1520x500xmm
Opmerkingen	y.o.b. 2001
Remarks	Surface 46 m2
Volume	12,0 dm ³
Gewicht	105 kg
Stock	3



Description

Used Goedhart DVS 61457

Used Goedhart DVS 61457 dubbel discharge evaporator with a Kelvion fan 45 cm in diameter, 035/0,22kW 1280/970 RPM. Min. workingtemp. -10°C max. 47°C. *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



DVS 7mm Technical data

Type DVS	3400V 50Hz 4-pole (1500 min ⁻¹ nom.)						3400V 50Hz 4-pole (1000 min ⁻¹ nom.)						Refrigerant										
	R507			R507			R507			R507			E1					E2					
	kW	kW	m ³ /h	kW	kW	m ³ /h	kW	kW	m ³ /h	kW	kW	m ³ /h	in	out	in	out	in	out	in	out	in	out	
31407	2,2	3,2	3467	52	2,2	2,3	2072	41	17	6	84	1056	1080	420	656	15	15	4419	2419	15	15	4419	2419
41407	4,0	4,0	3462	52	4,0	4,0	2072	41	23	6	93	1056	1180	420	656	22	22	4419	2419	22	22	4419	2419
61407	5,1	5,1	3271	52	5,1	3,7	1974	41	34	10	110	1056	1380	420	656	22	22	4419	2419	22	22	4419	2419
81407	6,3	6,3	3145	52	6,3	4,6	1919	41	46	12	128	1056	1580	420	656	22	22	4419	2419	22	22	4419	2419
31457	4,4	5,2	5267	56	4,4	3,7	3368	47	23	6	96	1056	1130	520	656	15	15	4419	2419	15	15	4419	2419
41457	5,4	6,4	5144	56	5,4	4,2	3296	47	30	8	106	1056	1230	520	656	16	16	4419	2419	16	16	4419	2419
61457	6,6	7,8	4918	56	6,6	5,8	3128	47	46	12	127	1056	1430	520	656	22	22	4419	2419	22	22	4419	2419
81457	7,7	9,3	4709	56	7,7	6,9	2973	47	61	16	148	1056	1630	520	656	22	22	4419	2419	22	22	4419	2419
31507	6,6	7,9	7601	63	6,6	5,3	5501	59	34	10	122	1356	1180	520	956	22	22	4419	2419	22	22	4419	2419
41507	8,7	10,4	7486	63	8,7	6,9	4870	59	45	12	134	1356	1280	520	956	22	22	4419	2419	22	22	4419	2419
61507	10,8	12,9	7263	63	10,8	9,0	4800	59	68	18	162	1356	1480	520	956	28	28	4419	2419	28	28	4419	2419
81507	12,6	15,1	7052	63	12,6	10,5	4672	59	91	24	190	1356	1680	520	956	28	28	4419	2419	28	28	4419	2419
31567	8,9	10,7	10722	63	7,7	7,5	6825	63	47	12	146	1456	1240	620	1056	22	22	4419	2419	22	22	4419	2419
41567	11,4	13,6	10537	63	9,8	8,4	6741	63	63	16	164	1456	1340	620	1056	22	22	4419	2419	22	22	4419	2419
61567	13,6	16,2	10297	63	11,3	11,3	6557	63	95	24	199	1456	1540	620	1056	28	28	4419	2419	28	28	4419	2419
81567	15,8	18,8	10034	63	14,5	14,5	6362	63	127	32	234	1456	1740	620	1056	28	28	4419	2419	28	28	4419	2419
31637	11,4	13,8	13095	63	9,8	9,8	9630	58	57	16	162	1456	1310	720	1056	28	28	4419	2419	28	28	4419	2419
41637	14,3	17,2	12921	63	12,2	12,2	9492	58	76	20	181	1456	1410	720	1056	28	28	4419	2419	28	28	4419	2419

Technical drawing of a compressor unit. The top view shows a rectangular unit with dimensions 200 mm (width) and 470 mm (depth). It features a central circular component and four mounting feet. The side view shows the unit's profile with dimensions 200 mm (width), 470 mm (depth), and 1140 mm (height). The side view also shows the unit's internal components, including the compressor and condenser coils. The drawing is labeled with 'DVS' and 'R507'.