

Carrier 30 RBS 140

Specifications

Marka	Carrier
Typ	30 RBS 140
Typ produktu	Air Cooled Chiller
Ogólna wydajność w kW	139,6
Ogólna wydajność w	39,7
Tonaż	
Czynnik chłodzący	Freon
Typ czynnika chłodzącego	R410a
Pump	✓
Rozmiary	2060x2270x1360 mm (LxWxH)
Compressor(s) type & model	4x Copeland ZP154KQE-TFD-604
Display	Carrier pro-dialog plus
Number of fans	2
Fan specifications	50 Hz - 0,54/0,18 kW - 720/500 RPM
Uwagi	y.o.b. 2013
Stock	1



Description

Used Carrier 30 RBS 140

Used Carrier 30 RBS 140 air cooled chiller with 4x Copeland ZP154KQE-TFD-604 scroll compressors. Condensor with 2 fans with max air flow of 10.600 m³/h. Pump Grundfos max waterflow 30 m³/h. This chiller has a Carrier Prodialog plus controller.

*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER	M2013016467
2 - MODELE - MODEL MODELLNUMMER	30RBS-140-0565-PE-
3 - VARIANTE VARIANT VARIANTE	NGAC
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSJAHR UND DATUM	28/05/2013
25 - FLUIDE PENDANT LE TRANSPORT MEDIUM DURING THE TRANSPORT FLÜSSIGKEIT WÄHREND DES TRANSPORTES	R410a 25.0 Kg
5 - FLUIDE - MEDIUM KÄLTENMITTEL	R 410 a
6 - GROUPE - GROUP	2
7 - CHARGES CIRCUIT A/B MEDIUM CHARGE A/B KREISLAUF A/B	12.50 Kg / 12.50 Kg
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM	23 AZOTE--NITROGEN--STICKSTOFF
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULÄSSIGE MIN/MAX -DRUCKE	(PS) -1.0 / 44.20 bar
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULÄSSIGE MIN/MAX -TEMPERATUREN	(TS) -20.0 / 68.0 °C
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK	44.2 bar
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSVENTIL -SOLLDRUCK	* bar
14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE UNIT LEAK TEST PRESSURE LECKTEST-DRUCK DES GERÄTS	17.0 bar
15 - TENSION VOLTAGE SPANNUNG	400 V 10 % 10 %
16 - PHASES PHASES PHASEN	3
17 - FREQUENCE FREQUENCY FREQUENZ	~ 50 Hz
18 - I MAXIMALE MAXIMUM AMPS MAXIMAL STROM	139.70 / *
19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME	65.40 / * KW
20 - PDS NET NET WEIGHT NETTOGEWICHT	881 Kg
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISK SETTING EINSTELLDRUCK DER WERTSCHREIBEN	* bar





