

Bitzer 6F-40.2Y-40P

Specifications

Marka	Bitzer
Typ	6F-40.2Y-40P
Czynnik chłodzący	Freon
kW at -5°C/+40°C	100,9
kW at -10°C/+40°C	83,1
kW at -20°C/+40°C	54,3
kW at -30°C/+40°C	33,0
kW at -40°C/+40°C	17,6
kW at -45°C/+40°C	11,7
Rozładunek	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	42 liter
Ssanie	✓
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m3 / h	151.6
Uwagi	y.o.b. 2010
Rozmiary	1500x800x1120 mm (LxWxH)
Stock	1



Description

Used Bitzer 6F-40.2Y-40P

Used Bitzer 6F-40.2Y-40P freeze-aggregate. Equipped with an AC&R oil separator, liquid receiver containing a volume of 42 liter, suction accumulator, liquid filter drier, pressure safety switches and multiple sight glasses. All mounted upon a steel base frame. The compressor has a headfan to exhaust excessive heat. Fan specs: Ziehl-Abegg functionable on both: 50 with 0,12 kW and 1410 RPM or 60 Hz with 0,19 kW and 1670 RPM. The diameter of the headfan is 300 mm.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.

*If requested we are happy to arrange



Your partner for used commercial and
industrial refrigeration equipment

your shipment.



Typ 6F-40.2Y-40P

S.Nr. 1678200060

BITZER KÜHLMASCHINENBAU GMBH

Made in E.C.

Nennspannung	Frequ.	Betr.strom	Anlaufstrom		Fördervol.	Drehzahl
V 3Ph~	Hz	A (max.)	A (Y)	A (YY)	m³/h	min ⁻¹
380-420	50	78	180	323	151.6	1450
440-480	60	78	180	323	183.0	1750

IP 54	ND/HD max.	19 / 28 bar
-------	------------	-------------

37302205



