

Sabroe SAB 128 HM MK3

Specifications

Marka	Sabroe
Typ	SAB 128 HM MK3
Czynnik chłodzący	NH 3 (ammonia)
kW at +10°C/+40°C	393,5
kW at 0°C/+40°C	272,8
kW at -5°C/+40°C	224,3
kW at -10°C/+40°C	182,6
kW at -20°C/+40°C	138,5
kW at -30°C/+40°C	86,8
kW at -40°C/+40°C	50,1
Silnik elektryczny Specs	50 Hz - 75 kW - 2945 RPM
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Przełączniki kondensacji ciśnienia	✓
Separator oleju	✓
Zawór elektromagnetyczny	✓
m ³ / h	635,0
Uwagi	Y.o.b. 2001
Rozmiary	2200x1250x170 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 128 HM MK3

Used Sabroe SAB 128 HM compressor unit on NH3. Complete with a Sabroe SAB 128 HM MK4 screw compressor, Leroy Somer elektromotor: 50 Hz - 75 kW - 2945 RPM, OHU 4119 oil separator with a volume of 270 liters, Alfa Laval PHE oil cooler, Marelli Motori MA 90L4 pump: 50 Hz - 1,5 kW - 1395 RPM and a Unisab 2 control panel.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





