

# Mycom N6WA

## Specifications

|                                         |                           |
|-----------------------------------------|---------------------------|
| Marka                                   | Mycom                     |
| Typ                                     | N6WA                      |
| Czynnik chłodzący                       | NH 3 (ammonia)            |
| kW at +10°C/+40°C                       | 346,6                     |
| kW at 0°C/+40°C                         | 233,1                     |
| kW at -5°C/+40°C                        | 187,2                     |
| kW at -10°C/+40°C                       | 147,9                     |
| kW at -20°C/+40°C                       | 86,1                      |
| Silnik elektryczny Specs                | 50 Hz - 30 kW - 1440 RPM  |
| Podstawa na stalowej ramie              | ✓                         |
| Ciśnieniowe przełączniki bezpieczeństwa | ✓                         |
| Wskaźniki ciśnienia                     | ✓                         |
| Separator oleju                         | ✓                         |
| Okno widokowe                           | ✓                         |
| Rozmiary                                | 1950x1350x2000 mm (LxWxH) |
| Stock                                   | 1                         |



## Description

### Used Mycom N6WA

Used Mycom N6WA reciprocating compressor on NH3 build by Mayekawa. Complete with a Leroy Somer PLS180L-T electric motor - 50 Hz - 30 kW - 1440 RPM, Mycom OSF 200-G oil separator with a volume of 30 liter and pressure and safety switches/gauges. The compressor has a capacity of 43,1 kW in booster conditions at the following temperatures: (-40°C/-10°C). It is possible to get this compressor with a different electric motor.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





