

Sabroe SAB 128 HM MK4

Specifications

Marka	Sabroe
Typ	SAB 128 HM MK4
Czynnik chłodzący	NH 3 (ammonia)
kW at +10°C/+40°C	416,8*
kW at 0°C/+40°C	300,3*
kW at -5°C/+40°C	251,5*
kW at -10°C/+40°C	208,5*
kW at -20°C/+40°C	138,5*
kW at -30°C/+40°C	86,8*
kW at -40°C/+40°C	50,1*
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Separator oleju	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓
m ³ / h	303 / 365
Uwagi	Y.o.b. 2003
Uwagi	*Capacity based on a bigger electric motor
Rozmiary	2200x1200x1600 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 128 HM MK4

Used Sabroe SAB 128 HM screw compressor on NH3. Complete with a Leroy-Somer PLS180M-T electric motor - 50 Hz - 30 kW - 2935 RPM, Sabroe OHU 4119 D oil separator with a volume of 270 liter, oil pump and a Unisab 2 display. The compressor has a displacement of 303 m³/h at 2950 RPM and 365 m³/h at 3550 RPM. *Capacity based at a bigger electric motor.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your shipment.





