

Sabroe SAB 163 HM

Specifications

Marka	Sabroe
Typ	SAB 163 HM
Czynnik chłodzący	NH 3 (ammonia)
kW at -5°C/+40°C	474,4
kW at -10°C/+40°C	386,8
kW at -20°C/+40°C	298,7
kW at -30°C/+40°C	184,5
kW at -40°C/+40°C	106,1
Silnik elektryczny Specs	50 Hz - 132 kW - 2945 RPM
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Separator oleju	✓
Panel kontrolny	✓
m ³ / h	635
Uwagi	Y.o.b. 2005
Rozmiary	2800x1500x2100 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 163 HM

Used Sabroe SAB 163 HM NH₃ screw compressor on a steel base frame. Complete with a Leroy Somer PLS280MP-T electric motor - 50 Hz - 132 kW - 2945 RPM, Sabroe OHU 4123D oil separator with a volume of 410 liter, oil pump and a Unisab 2 control panel. The compressor has a displacement of 635 m³/h at 2950 RPM. Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.





