

Grasso M-3 / MB-3BG

Specifications

Marka	Grasso
Typ	M-3 / MB-3BG
Czynnik chłodzący	NH 3 (ammonia)
kW at 0°C/+40°C	637,0*
kW at -10°C/+40°C	350,0**
kW at -30°C/+40°C	165,0***
Silnik elektryczny Specs	50/60 Hz - 132/152 kW - 2970/3570 RPM
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Separator oleju	✓
Panel kontrolny	✓
m ³ / h	690,0
Uwagi	Y.o.b. 2001
Uwagi	Capacity based at: *(0°C/+35°C) - **(-15°C/+35°C) - ***(-35°C/+35°C)
Rozmiary	3050x1200x2200 mm (LxWxH)
Stock	1



Description

Used Grasso M-3 / MB-3BG

Used Grasso MB-3BG compressor unit on NH₃. Complete with 1 Grasso M-3 screw compressor, Schorch KN7280M-AB01B-Z electric motor - 50/60 Hz - 132/152 kW - 2970/3570 RPM, Grasso 250/2000/2 oil cooler, Grasso DM508 oil separator with a volume of 275 liter and a Grasso GSC display. The compressor has a displacement of 690 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also arrange the logistics.







