

Bitzer 4G.2

Specifications

Marka	Bitzer
Typ	4G.2
Czynnik chłodzący	Freon
kW at 0°C/+40°C	70,9
kW at -5°C/+40°C	58,7
kW at -10°C/+40°C	48,2
kW at -20°C/+40°C	31,2
kW at -30°C/+40°C	18,8
kW at -40°C/+40°C	10,1
kW at -45°C/+40°C	6,8
Rozładunek	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Separator oleju	✓
m ³ / h	102
Uwagi	Y.o.b. 2011
Rozmiary	1140x660x910 mm (LxWxH)
Stock	1



Description

Used Bitzer 4G.2

Used Bitzer 4G.2 open-type reciprocating compressor on Freon with a sight glass. Complete with a elektrim electric motor, AC&R S-5692 oil separator with a volume of 6,7 liter and pressure and safety switches/gauges. The compressor has a displacement of 102 m³/h at 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.



