

Bitzer S6G-25.2Y-40P

Specifications

Marka	Bitzer
Typ	S6G-25.2Y-40P
Czynnik chłodzący	Freon
kW at -30°C/+40°C	30,1
kW at -40°C/+40°C	21,3
kW at -45°C/+40°C	17,4
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Ssanie	✓
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓
m ³ / h	84,5 - 101,98
Uwagi	Y.o.b. 2008
Rozmiary	2000x700x1080 mm (LxWxH)
Stock	1



Description

Used Bitzer S6G-25.2Y-40P

Used Bitzer S6G-25.2Y-40P two-stage semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F552T liquid receiver, suction accumulator, oil separator, braced heat exchanger, liquid line filter drier, pressure and safety switches/gauges and a control panel. The compressor has a displacement of 84,5 m³/h at 1450 RPM and 102 m³/h at 1750 RPM. *Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.







