

## Bitzer 4G.2Y (x1) & 4G.2 (x1)

### Specifications

|                                         |                                             |
|-----------------------------------------|---------------------------------------------|
| Marka                                   | Bitzer                                      |
| Typ                                     | 4G.2Y (x1) & 4G.2 (x1)                      |
| Czynnik chłodzący                       | Freon                                       |
| kW at 0°C/+40°C                         | 141,8                                       |
| kW at -5°C/+40°C                        | 117,5                                       |
| kW at -10°C/+40°C                       | 96,3                                        |
| kW at -20°C/+40°C                       | 62,4                                        |
| kW at -30°C/+40°C                       | 37,7                                        |
| kW at -40°C/+40°C                       | 20,2                                        |
| Rozładunek                              | ✓                                           |
| Kontrolka wydajności                    | ✓                                           |
| Podstawa na stalowej ramie              | ✓                                           |
| Ciśnieniowe przełączniki bezpieczeństwa | ✓                                           |
| Wskaźniki ciśnienia                     | ✓                                           |
| Separator oleju                         | ✓                                           |
| Okno widokowe                           | ✓                                           |
| Zawór elektromagnetyczny                | ✓                                           |
| m <sup>3</sup> / h                      | 204                                         |
| Uwagi                                   | Y.o.b. 1996 - 4G.2 &<br>Y.o.b. 2010 - 4G.2Y |
| Package / Rack                          | ✓                                           |
| Rozmiary                                | 1200x1100x750 mm<br>(LxWxH)                 |
| Stock                                   | 1                                           |



### Description

#### Used Bitzer 4G.2Y (x1) & 4G.2 (x1)

Used Bitzer open-type reciprocating with 4G.2 & 4G.2Y compressors on Freon. Complete with a Rotor XC160L04 electric motor (x2) - 50 Hz - 15 kW - 1460 RPM, AC&R S-5692X oil separator, pressure and safety switches/gauges and sight glass. The compressors has a displacement of 204 m<sup>3</sup>/h at 1750 RPM.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. \*If requested we are happy to arrange your shipment.



















