

Sabroe SAB 128 HM MK2 man VI

Specifications

Marka	Sabroe
Typ	SAB 128 HM MK2 man VI
Czynnik chłodzący	NH 3 (ammonia)
kW at +10°C/+40°C	393,5
kW at 0°C/+40°C	272,8
kW at -5°C/+40°C	224,3
kW at -10°C/+40°C	182,6
kW at -20°C/+40°C	138,5
kW at -30°C/+40°C	86,8
kW at -40°C/+40°C	50,1
Rozładunek	✓
Kontrolka wydajności	✓
m ³ / h	455 m ³ /h at 2950 RPM / 548 m ³ /h at 3550 RPM
Uwagi	Y.o.b. 2009
Rozmiary	930x830x620 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 128 HM MK2 man VI

Used Sabroe SAB 128 HM screw compressor on NH₃ (Ammonia). The compressor has a displacement of 455 m³/h at 2950 RPM and 548 m³/h at 3550 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.

