

Bitzer 6G-40.2Y

Specifications

Marka	Bitzer
Typ	6G-40.2Y
Czynnik chłodzący	Freon
kW at 0°C/+40°C	102,6
kW at -5°C/+40°C	85,4
kW at -10°C/+40°C	70,3
kW at -20°C/+40°C	46,0
kW at -30°C/+40°C	28,0
kW at -40°C/+40°C	14,9
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Przełączniki kondensacji ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	105
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m3 / h	50 Hz - 126,8 m³/h / 60 Hz - 152,9 m³/h
Uwagi	Y.o.b. 2000
Waga kg.	+ - 550 kg



	(LxWxH)
Bitzer	2000x900x1850 mm

Description

Used Bitzer 6G-40.2Y

Used Bitzer 6G-40.2Y semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F1052T liquid receiver with a volume of 105 liters, AC&R S-5694 oil separator, liquid line filter drier, and pressure and safety switches/gauges. The compressor has a displacement of 126,8 m³/h at 50 Hz and 152,9 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.





