

Bitzer 6G.2

Specifications

Marka	Bitzer
Typ	6G.2
Czynnik chłodzący	Freon
kW at 0°C/+40°C	106,3
kW at -5°C/+40°C	88,0
kW at -10°C/+40°C	72,2
kW at -20°C/+40°C	46,8
kW at -30°C/+40°C	28,3
kW at -40°C/+40°C	15,2
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	125 l
Okno widokowe	✓
m ³ / h	50 Hz - 78,7 m ³ /h / 60 Hz - 153,0 m ³ /h
Rozmiary	2100x780x1260 mm (LxWxH)
Stock	1



Description

Used Bitzer 6G.2

Used Bitzer 6G.2 open-type reciprocating compressor on Freon. Complete with a VDB 0530 electric motor - 50 Hz - 30 kW - 1465 RPM, Stahlbau Hopfgarten liquid receiver with a volume of 125 liters, pressure and safety switches and a sight glass. The compressors have a displacement of 50/60 Hz - 78,7/153,0 m³/h - 1450/1750 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive quality test and after it has been cleaned industrially.
*If requested we are happy to arrange your shipment.





