

Bitzer 4H-25.2 (x2) / 44H-50.2

Specifications

Marka	Bitzer
Typ	4H-25.2 (x2) / 44H-50.2
Czynnik chłodzący	Freon
kW at 0°C/+40°C	118,9
kW at -5°C/+40°C	98,7
kW at -10°C/+40°C	81,2
kW at -20°C/+40°C	52,8
kW at -30°C/+40°C	31,8
kW at -40°C/+40°C	16,6
Rozładunek	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	105
Ssanie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
m3 / h	50 Hz - 147,2 m³/h / 60 Hz - 177,6 m³/h
Uwagi	Y.o.b. 2000
Package / Rack	✓



	(LxWxH)
Bitzer rack	2150x900x1090 mm

Description

Used Bitzer 4H-25.2 (x2) / 44H-50.2

Used Bitzer 4H-25.2 (x2) / 44H-50.2 semi-hermetic reciprocating compressor rack on Freon. Complete with a Bitzer F 1052 liquid receiver with a volume of 105 liter, suction accumulator, liquid line filter drier and pressure and safety switches. The set has a total displacement of 147,2 m³/h at 50 Hz & 177,6 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.





