

Bitzer 4H-25.2Y-40P

Specifications

Marka	Bitzer
Typ	4H-25.2Y-40P
Czynnik chłodzący	Freon
kW at 0°C/+40°C	59,4
kW at -5°C/+40°C	49,4
kW at -10°C/+40°C	40,6
kW at -20°C/+40°C	26,4
kW at -30°C/+40°C	15,9
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	54
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m3 / h	50 Hz - 73,7 m ³ /h / 60 Hz - 88,9 m ³ /h
Uwagi	Y.o.b. 2011
Rozmiary	1700x520x740 mm (LxWxH)
Stock	1



Description

Used Bitzer 4H-25.2Y-40P

Used Bitzer 4H-25.2Y-40P semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F550T liquid receiver with a volume of 54 liter, oil separator, pressure and safety switches and a liquid line filter drier. The compressor has a displacement of 73,7 m³/h at 50 Hz & 88,9 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also arrange the logistics.



