

Bitzer OSNA 8591-K (x3) & OSKA 7471-K (x2)

Specifications

Marka	Bitzer
Typ	OSNA 8591-K (x3) & OSKA 7471-K (x2)
Czynnik chłodzący	NH 3 (ammonia)
kW at +10°C/+40°C	*662,8
kW at 0°C/+40°C	*456,4
kW at -5°C/+40°C	*373,0
kW at -10°C/+40°C	1024,1 / *301,0
kW at -20°C/+40°C	768,0**
kW at -30°C/+40°C	480,9**
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Separator oleju	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓



	OSKA 7471-K : 50 Hz - 250 m ³ /h / 60 Hz - 690 m ³ /h
Wzrost	OSNA 8591-K (x3) : 50 Hz - 804 m ³ /h
Uwagi	**Capacities are based on 2 OSKA 7471-K compressors
Uwagi	**Capacity based on an economizer
Package / Rack	✓
Rozmiary	7250x2250x2500 mm (LxWxH)
Stock	1

Description

Used Bitzer OSNA 8591-K (x3) & OSKA 7471-K (x2)

Used Bitzer OSNA 8591-K (x3) & OSKA 7471-K (x2) screw compressor set on NH3 (Ammonia). Complete with an oil separator, oil cooler, 2 Vacon NXS drives and a control cabinet. The OSNA 8591-K have a displacement of 804 m³/h at 50 Hz & 2214 m³/h at 60 Hz and the OSKA 7471-K have a displacement of 250 m³/h at 50 Hz & 690 m³/h at 60 Hz. **Capacity based on an economizer.

Please notice that the 2 pieces of Bitzer OSKA 7171-K where used to make warm water.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.







