

Helpman HTC 100-133-V 420 PREP

Specifications

Marka	Helpman
Typ	HTC 100-133-V 420 PREP
Typ produktu	Drycooler
Ogólna wydajność w kW	145,0*
Liczba wentylatorów	3
Prdkość obrotów wentylatora (obr/min)	380/250 & 350/200
Czynnik chłodzący	Glycol
Przepływ powietrza w m ³ /h	43.500
wentylatory o średnicy Ø 1000 mm	
Powierzchnia (m2)	685 m ²
Objętość rurki	54 dm ³
Rozmiary	5970x1300x1450 mm (LxWxH)
Waga	832 kg
Uwagi	Y.o.b. 2002
Remarks	*Capacity is based on a medium inlet temperature of 60°C and an outlet temperature of 40°C
Stock	1



Description

Used Helpman HTC 100-133-V 420 PREP

Used Helpman HTC 100.133-V 420 PREP drycooler. Complete with 3 Ziehl-Abegg FE100-NDS.6N.6 fans - 50/60 Hz - 380/250 - 350/200 RPM - 0,67/0,33 - 0,84/0,32 kW and a diameter of 1000 mm and an airflow of 43.500 m³/h. The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 145,0kW with a medium inlet temperature of 60°C and an outlet temperature of 40°C.

*All components of this used condensers will be tested on good working, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered.



**Your partner for used commercial and
industrial refrigeration equipment**

Also, we can arrange your shipment.



