

Bitzer 6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1)

Specifications

Marka	Bitzer
Typ	6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1)
Czynnik chłodzący	Freon
kW at -5°C/+40°C	166,9
kW at -10°C/+40°C	137,5
kW at -20°C/+40°C	90,1
kW at -30°C/+40°C	54,9
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	160 l
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m ³ / h	50 Hz - 247,9 m ³ /h / 60 Hz - 299,0 m ³ /h
Uwagi	Y.o.b. 2004
Package / Rack	✓



(LxWxH)

Bitzer

3100x920x2100 mm

Description

Used Bitzer 6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1)

Used 6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1) semi-hermetic reciprocating compressor rack on Freon. Complete with a Bitzer F1602N liquid receiver with a volume of 160 liters, Henry Technologies S-5202-CE oil separator, AC&R S-9109-CE oil reservoir, brazed heat exchanger, pressure and safety switches/gauges and liquid line filter drier.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.







