

Bitzer 6G-40.2Y-40P

Specifications

Marka	Bitzer
Typ	6G-40.2Y-40P
Czynnik chłodzący	Freon
kW at 0°C/+40°C	102,6
kW at -5°C/+40°C	85,4
kW at -10°C/+40°C	70,3
kW at -20°C/+40°C	46,0
kW at -30°C/+40°C	28,0
kW at -40°C/+40°C	14,9
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	160 l
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m ³ / h	50 Hz - 126,8 m ³ /h / 60 Hz - 152,9 m ³ /h
Uwagi	Y.o.b. 2003
Rozmiary	1400x870x2420 mm (LxWxH)
Stock	1



Description

Used Bitzer 6G-40.2Y-40P

Used Bitzer 6G-40.2Y-40P semi-hermetic reciprocating compressor unit. Complete with a Bitzer FS1602 liquid receiver with volume of 160 liters, Henry Technologies S-5694-CE oil separator, pressure and safety switches/gauges, Danfoss liquid line filter drier and a sight glass. The displacement of the compressor is 126,8 m³/h at 50 Hz and 152,9 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning.

*Optionally we can also perform a new paint job and arrange the logistics.





