

Güntner GFH 102C/2*3 S (D)-F4 /3

Specifications

Marka	Güntner
Typ	GFH 102C/2*3 S (D)-F4 /3
Typ produktu	Drycooler
Ogólna wydajność w kW	250,6
Liczba wentylatorów	6
Prdkość obrotów wentylatora (obr/min)	430/310
Czynnik chłodzący	Glycol
Przepływ powietrza w m ³ /h	84.500
wentylatory o średnicy Ø 1000 mm	
Powierzchnia (m ²)	1190,5
Objętość rurki	221 dm ³
Rozmiary (LxWxH)	7260x2400x1500 mm
Stock	4



Description

Used Güntner GFH 102C/2*3 S (D)-F4 /3

Used Güntner GFH 102C/2*3S (D)-F4 /3 drycooler. Complete with 6 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,50/0,19 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 84.500 m³/h.

*Capacity based on the following:

Air inlet/outlet temperature: 25°C/33,9°C.

Medium Inlet/outlet temperature: 40°C/35°C.

Volume flow: 47,1 m³/h.

Medium: Glycol 34%.

Capacity of 625,1 kW based on the following:

Air inlet/outlet temperature: 25°C/47,3°C.

Medium Inlet/outlet temperature:
60°C/40°C.

Volume flow: 29,3 m³/h.

Medium: Glycol 34%.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.





