

Bitzer 6F-50.2Y-40P Condensing unit

Specifications

Marka	Bitzer
Typ	6F-50.2Y-40P Condensing unit
Czynnik chłodzący	Freon
kW at 0°C/+40°C	121,7
kW at -5°C/+40°C	101,3
kW at -10°C/+40°C	83,6
kW at -20°C/+40°C	55,0
kW at -30°C/+40°C	33,9
kW at -40°C/+40°C	18,6
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	70
Ssanie	✓
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Panel kontrolny	✓
m ³ / h	151,6 m ³ /h at 50 Hz & 183 m ³ /h at 60 Hz
Uwagi	Y.o.b. 2013
Condensing Unit	✓



Rozmiar	3240x1100x2320 mm (LxWxH)
Stock	3

Description

Used Bitzer 6F-50.2Y-40P Condensing unit

Used Fredvic UM 500 MT/S condensing unit on Freon. Complete with a Bitzer 6F-50.2Y-40P semi-hermetic reciprocating compressor, condenser with 3 EBM-Papst fans - 50 Hz - 1,94/1,21 kW - 880/670 RPM, OCS liquid receiver with a volume of 70 liter, suction accumulator, oil separator, liquid line filter drier, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 151,6 m³/h at 50 Hz & 183 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also arrange the logistics.







