

Bitzer 6J-22.2Y-40P (x2) & 66J-44.2Y-40P

Specifications

Marka	Bitzer
Typ	6J-22.2Y-40P (x2) & 66J-44.2Y-40P
Czynnik chłodzący	Freon
kW at -5°C/+40°C	127,8
kW at -10°C/+40°C	105,2
kW at -20°C/+40°C	68,8
kW at -30°C/+40°C	41,8
kW at -40°C/+40°C	22,6
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m ³ / h	190,6 m ³ /h at 50 Hz & 230 m ³ /h at 60 Hz
Uwagi	Y.o.b. 2006
Package / Rack	✓
Rozmiary	2750x1000x1950 mm (LxWxH)
Stock	1



Description

Used Bitzer 6J-22.2Y-40P (x2) & 66J-44.2Y-40P

Used Bitzer 6J-22.2Y-40P (x2) semi-hermetic reciprocating tandem compressor on Freon. Complete with a Bitzer 4DC-5.2Y-40S which provides the subcooling of the liquid to the evaporators. This application achieves a considerable energy saving compared to a conventional system. Further the set comes with a Bitzer liquid receiver, Henry S-5694-CE oil separator, Henry S-9109-CE oil reservoir, brazed heat exchanger and pressure and safety switches/gauges. The tandem compressor has a total displacement of 190,6 m³/h at 50 Hz & 230 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all



equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.





