

Stal S83A-HP

Specifications

Marka	Stal
Typ	S83A-HP
Czynnik chłodzący	NH 3 (ammonia)
kW at -30°C/+40°C	331,9
kW at -40°C/+40°C	192,7
kW at -45°C/+40°C	143,9
Silnik elektryczny Specs	50 Hz - 200 kW - 2965 RPM
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Separator oleju	✓
Panel kontrolny	✓
m ³ / h	1780
Rozmiary	3500x1350x1600 (LxWxH)
Stock	1



Description

Used Stal S83A-HP

Used ABB Stal SVA 83E compressor skid on NH3. Complete with a Stal S83A screw compressor and a Schorch KN7315M-AB019-160 electric motor - 50 Hz - 200 kW - 2965 RPM, oil separator, oil cooler, oil filter, pressure and safety switches/gauges and a control panel with an ABB Stalectronic 700 controller. The compressor has a displacement of 1740 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.







