

# Sabroe HPO 28

## Specifications

Marka	Sabroe
Typ	HPO 28
Czynnik chłodzący	CO2
Refrigerant type	R744
kW at -20°C/+40°C	611,4*
kW at -30°C/+40°C	418,1*
kW at -40°C/+40°C	271,1*
Silnik elektryczny Specs	50 Hz - 132 kW - 1487 RPM
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Separator oleju	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓
m <sup>3</sup> / h	233
Uwagi	Y.o.b. 2012
Uwagi	*Capacity based on a condensing temperature of 0°C
Rozmiary	2500x950x1700 mm (LxWxH)
Stock	2



## Description

### Used Sabroe HPO 28

Used Sabroe HPO 28 reciprocating compressor on R744 (CO<sub>2</sub>). Complete with an ABB M2BAT 315 SMB 4 electric motor - 50 Hz - 132 kW - 1487 RPM, Sabroe OVUR 4113D oil separator with a volume of 158 liter and a Unisab 3 controller. The compressor has a displacement of 233 m<sup>3</sup>/h. \*Capacity based on a condensing temperature of 0°C.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive quality test and after it has been cleaned industrially. \*If requested we are happy to arrange your shipment.





