

## Bitzer HSN 7461-70-40P (x2)

### Specifications

Marka	Bitzer
Typ	HSN 7461-70-40P (x2)
Czynnik chłodzący	Freon
kW at -20°C/+40°C	229,6
kW at -30°C/+40°C	157,4
kW at -40°C/+40°C	102,0
kW at -45°C/+40°C	79,8
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	228
Ssanie	✓
Separator oleju	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓
m <sup>3</sup> / h	50 Hz - 440 m <sup>3</sup> /h / 60 Hz - 528 m <sup>3</sup> /h at 60 Hz
Uwagi	Y.o.b. 2014
Package / Rack	✓



---

	(LxWxH)
Bitzerkiary	2950x1710x2500 mm

---

## Description

### Used Bitzer HSN 7461-70-40P (x2)

New Bitzer HSN 7461-70-40P (x2) semi-hermetic screw compressor on Freon. Complete with a Bitzer OA4188 oil separator with a volume of 88 liter, Bitzer OW401B oil cooler, Bitzer F2202N liquid receiver with a volume of 228 liter, Henry S-7741-CE accumulator, GEA GBS 700M-AE-30 brazed heat exchanger as economizer and pressure and safety switches/gauges. The compressor has a displacement of 440 m<sup>3</sup>/h at 50 Hz & 528 m<sup>3</sup>/h at 60 Hz.

Please notice that 1 compressor is missing at this moment, but we can deliver this set with 2 compressors. Feel free to contact us for more information!

\*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.







