

Aermec ANL030°A°°°°°

Specifications

Marka	Aermec
Typ	ANL030°A°°°°°
Typ produktu	Air Cooled Chiller
Ogólna wydajność w kW	7,5
Ogólna wydajność w	2,1
Tonaż	
Czynnik chłodzący	Freon
Typ czynnika chłodzącego	R410A
Pump	✓
Waga kg.	103
Rozmiary	1150x400x1020 mm (LxWxH)
Compressor(s) type & model	x1 Copeland ZP32K3ETFD 400/3
Display	Aermec display
Number of fans	1
Fan specifications	50/60 Hz - 0,14/0,19 kW - 870/930 RPM
Uwagi	Y.o.b. 2013
Stock	1




Description

Used Aermec ANL030°A°°°°°

Used Aermec ANL030°A°°°°° air-cooled chiller on Freon R410A. Complete with a 1 Copeland ZP32K3ETFD 400/3 scroll compressor, condenser with 1 Ebm-papst A6E450-AQ15-12 fan - 50/60 Hz - 0,14/0,19 kW - 870/930 RPM, coaxial evaporator, Wilo TOP-RL25/8,5AE water pump, Zilmet expansion vessel and a control cabinet with a Aermec display. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks, compressors, fans, control panel and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



AERMEC		AERMEC S.p.A. Formigosa 37040-Beyllacqua (VI)-ITALIA		EUROVENT REGISTERED PERFORMANCE		CE	
ANL030°A°°°°°				Made in Italy			
3N~400V 50 Hz		N° 1303005163960002		comm/vers 5		IP X4 P. date 2013	
30-35 °C		40-45 °C		47-55 °C		12-7 °C	
7/6°C (DB/WB)		7/6°C (DB/WB)		7/6°C (DB/WB)		35 °C	
PH[kW]	0.00	PH[kW]	0.00	PH[kW]	0.00	PC[kW]	7.50
PE[kW]	0.00	PE[kW]	0.00	PE[kW]	0.00	PE[kW]	2.61
COP[W/W]	0.0	COP[W/W]	0.0	COP[W/W]	0.0	EER[W/W]	2.87
In[A]	0.00	In[A]	0.00	In[A]	0.00	In[A]	5.70
RES EL / EL HEATER	[kW]	0.00	Is[A]	37	Imax[A]	7.70	
RES EL / EL HEIZUNG	[A]	0.00	R410A	[Kg]	1.56		
TS (HP/LP) [°C]	Min -10 / -16	PS (HP/LP) [bar]	42 / 25	Versione SW: 4.4.2			
	Max 120 / 52						
							
ANL030°A°°°°°-1303005163960002							



