

Bitzer 4N-20.2 Y (x3)

Specifications

Marka	Bitzer
Typ	4N-20.2 Y (x3)
Czynnik chłodzący	Freon
kW at 0°C/+40°C	137,4
kW at -5°C/+40°C	114,3
kW at -10°C/+40°C	93,9
kW at -20°C/+40°C	61,2
kW at -30°C/+40°C	37,2
kW at -40°C/+40°C	19,2
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	7,4
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter linii cieczy	✓
Okno widokowe	✓
m ³ / h	50 Hz - 168,3 m ³ /h & 60 Hz - 203,1 m ³ /h
Package / Rack	✓
Rozmiary	2115x1500x1200 mm (LxWxH)
Stock	1



Description

Used Bitzer 4N-20.2 Y (x3)

Used Bitzer 4N-20.2 Y (x3) semi-hermetic reciprocating compressors on Freon. Complete with a Carly HCYR 81 oil receiver, Temprite 926 L oil separator, pressure and safety switches/gauges, oil level system AC&R and a filter drier. The compressors have a total displacement of 168,3 m³/h at 50 Hz & 203,1 m³/h at 60 Hz. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





