

# Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit

## Specifications

Marka	Bitzer
Typ	4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit
Czynnik chłodzący	Freon
kW at 0°C/+40°C	82,3
kW at -5°C/+40°C	65,5
kW at -10°C/+40°C	51,4
kW at -20°C/+40°C	29,4
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Panel kontrolny	✓
m <sup>3</sup> / h	161,1
Uwagi	Y.o.b. 2014
Package / Rack	✓
Rozmiary	2300x1400x1400 mm (LxWxH)
Stock	1



## Description

### Used Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit

Used Rivacold RV4C1103-1 compressor unit on Freon. Complete with a Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) semi-hermetic reciprocating compressors, Ocs cold OCS-08 oil reservoir, Henry Technologies S-1901-CE oil separator, pressure and safety switches/gauges and a control cabinet with a Carel pR100 controller and Carel display. The compressors have a total displacement of 161,1 m<sup>3</sup>/h. The capacity is based on the use of Freon type: R134A.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all



equipment including an extensive test, warranty and industrial cleaning.  
\*Optional we can also perform a new paint job and arrange the logistics.



**RIVACOLD**  
 Via Stella,7 - Montecchio 61022 Vallefoglia(PU)ITALY  
 Tel. +39 - 0721 - 919911 r.a. Fax +39 - 0721 - 480015  
 Internet:www.rivacold.com Mail:info@rivacold.com

CE

Code : **RV4C1103 - 1**

Volt/Ph/Hz : 400/3/50	Comp. : 4NES - 14Y 4PES
W : 46950	HP : 14X2 10X1
Win : 22620	In (A) : 43.57
W defrost :	
Gas : R134A	Kg :
PS Hp : 20 bar	PS Lp : 14 bar
TS Hp : -10/100 °C	TS Lp : -40/100 °C

S/N : **14401384**

Direttiva 97/23/CE del 29.05.1997 (P.E.D.) Cat. III - Prodotto nel 20/14

0948 0 060144 013843









