

# Bitzer 4VES-10Y-40P (x1) & 4FE-25Y-40P (x1) Condensing Unit

## Specifications

Marka	Bitzer
Typ	4VES-10Y-40P (x1) & 4FE-25Y-40P (x1) Condensing Unit
Czynnik chłodzący	Freon
Refrigerant type	R134a
kW at 0°C/+40°C	70,2
kW at -5°C/+40°C	56,6
kW at -10°C/+40°C	45,0
kW at -20°C/+40°C	27,2
Kontrolka wydajności	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	80
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Panel kontrolny	✓
m <sup>3</sup> / h	136,5
Uwagi	Y.o.b. 2010
Condensing Unit	✓



(LxWxH)

Bitzerkiary

4100x1300x2200 mm

## Description

### Used Bitzer 4VES-10Y-40P (x1) & 4FE-25Y-40P (x1) Condensing Unit

Used Rivacold RV4C0192 condensing unit on Freon. Complete with a Bitzer 4VES-10Y-40P (x1) & 4FE-25Y-40P (x1) semi-hermetic reciprocating compressors, condenser with 3 fans, Frigo Mec 324/1113VK01-FSR liquid receiver, OCS RLTU28 liquid receiver with volume of 27,5 liters, Henry Technologies S-5692 CE oil separator, OCS-08 RLTU8 olie reservoir, pressure and safety switch, 2 Danfoss frequency regulators and a control cabinet with a 2 Danfoss controllers and 2 Danfoss displays. The compressors have a total displacement of 136,5 m<sup>3</sup>/h at 50 Hz. The capacity is based on the use of Freon type: R134a.

\*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.









