

# Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

## Specifications

Marka	Bitzer
Typ	4TCS-12.2Y-40P (x2) Condensing unit
Czynnik chłodzący	Freon
kW at 0°C/+40°C	64,2
kW at -5°C/+40°C	52,1
kW at -10°C/+40°C	41,8
kW at -20°C/+40°C	25,7
kW at -30°C/+40°C	14,5
Kontrolka wydajności	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	80
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Panel kontrolny	✓
m <sup>3</sup> / h	82,6
Uwagi	Y.o.b. 2009
Condensing Unit	✓
Rozmiary	4100x1300x2200 mm (LxWxH)
Stock	1



## Description

### Used Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Used Rivacold RV4C0278 condensing unit on Freon. Complete with a Bitzer x2 4TCS-12.2Y-40P semi-hermetic reciprocating compressors, condenser with 3 Ziehl-Abegg FE080-NDS.6K.V7 fans - 50 Hz - 0,37/0,20 kW - 440/340 RPM, Frigo Mec 324/1113VK01-FSR liquid receiver, OCS liquid receiver, Henry Technologies S-5690-CE oil separator, OCS-08 RLTU8 oil reservoir, 2 Danfoss frequency regulators and a control cabinet with a 2 Danfoss controllers and 2 Danfoss displays. The compressors have a total displacement of 82,6 m<sup>3</sup>/h at 50 Hz and 99,8 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only



the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.









