

# Bitzer 4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1)

## Specifications

Marka	Bitzer
Typ	4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1)
Czynnik chłodzący	Freon
kW at 0°C/+40°C	107,8
kW at -5°C/+40°C	89,3
kW at -10°C/+40°C	73,5
kW at -20°C/+40°C	47,6
kW at -30°C/+40°C	28,7
kW at -40°C/+40°C	14,9
kW at -45°C/+40°C	9,8
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓



m3 / h	136,6
Uwagi	Y.o.b. 2001
Package / Rack	✓
Rozmiary	2900x1000x1690 mm (LxWxH)
Stock	1

## Description

### **Used Bitzer 4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1)**

Used Bitzer 4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1) semi-hermetic reciprocating compressors rack on Freon. Complete with a x1 Bitzer FS 302 and x1 Bitzer FS 562 liquid receivers, x2 AC&R S-9108U oil reservoirs, x1 AC&R S-5188 and x1 AC&R S-5192 oil separators, pressure and safety switches and a liquid line filters drier. The compressors have a total displacement of 136,6 m<sup>3</sup>/h at 50 Hz and 163,1 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.









