

Bitzer 6F-40.2Y (x2) & 6FF-80.2Y

Specifications

Marka	Bitzer
Typ	6F-40.2Y (x2) & 6FF-80.2Y
Czynnik chłodzący	Freon
kW at -5°C/+40°C	202,0
kW at -10°C/+40°C	166,2
kW at -20°C/+40°C	108,5
kW at -30°C/+40°C	65,9
kW at -40°C/+40°C	35,1
kW at -45°C/+40°C	23,4
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓
m ³ / h	50 Hz - 303,2 m ³ /h & 60 Hz - 362 m ³ /h
Package / Rack	✓
Rozmiary	2550x2150x1800 mm (LxWxH)
Stock	1



Description

Used Bitzer 6F-40.2Y (x2) & 6FF-80.2Y

Used Bitzer 6F-40.2Y (x2) & 6FF-80.2Y semi-hermetic reciprocating compressor Freon. Complete with pressure and safety switches/gauges, Vacon frequency regulator and a control cabinet with a Siemens OP7-DP controller. The compressors have a total displacement of 303,2 m³/h at 50 Hz & 362 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





