

# Maneurop MTZ 36 JG 4A VE Condensing unit

## Specifications

|   |                                    |
|---|------------------------------------|
| Marka                                   | Maneurop                           |
| Typ                                     | MTZ 36 JG 4A VE<br>Condensing unit |
| Czynnik chłodzący                       | Freon                              |
| kW at +10°C/+40°C                       | 12,2                               |
| kW at 0°C/+40°C                         | 8,2                                |
| kW at -5°C/+40°C                        | 6,6                                |
| kW at -10°C/+40°C                       | 5,3                                |
| kW at -20°C/+40°C                       | 3,1                                |
| kW at -30°C/+40°C                       | 1,6                                |
| Podstawa na stalowej ramie              | ✓                                  |
| Ciśnieniowe przełączniki bezpieczeństwa | ✓                                  |
| Obiornik cieczy                         | ✓                                  |
| Obiornik cieczy ltr.                    | 12                                 |
| Osuszający filter lini cieczy           | ✓                                  |
| Okno widokowe                           | ✓                                  |
| Panel kontrolny                         | ✓                                  |
| m <sup>3</sup> / h                      | 10,5                               |
| Condensing Unit                         | ✓                                  |
| Rozmiary                                | 1000x1400x1000 mm<br>(LxWxH)       |
| Stock                                   | 1                                  |



## Description

### Used Maneurop MTZ 36 JG 4A VE Condensing unit

Used Maneurop MTZ 36 JG 4A VE condensing unit on Freon. Complete with a Maneurop piston compressor, condenser with 2 FMV S400-VD41 fans - 50 Hz - 145 W - 1500 RPM - diameter 400 mm, Apparatebau Hopfgarten ZHP12 liquid receiver with a volume of 12 liter, liquid line filter drier, pressure and safety switch and a control cabinet. The compressor has a displacement of 10,5 m<sup>3</sup>/h.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also



perform a new paint job and arrange the logistics.





