

Bitzer 4H.2 / 6G.2 / 6F.2

Specifications

Marka	Bitzer
Typ	4H.2 / 6G.2 / 6F.2
Czynnik chłodzący	Freon
kW at -10°C/+40°C	190
kW at -20°C/+40°C	124,5
kW at -30°C/+40°C	76,2
kW at -40°C/+40°C	41,5
Silnik elektryczny Specs	16 / 30 / 37
Rozładunek	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	20
Separator oleju	✓
Osuszający filter lini cieczy	✓
Panel kontrolny	✓
Uwagi	# // Electromotor 16 kW at 1445 RPM (4H.2) // 30 kW at 1475 RPM (6H.2) // 37 kW at 1480 RPM (6F.2) // Evaporator Helpman PLV 24-4



	freon types
Warranty	8400x1700x2500mm (LxWxH)
Stock	1

Description

Used Bitzer 4H.2 / 6G.2 / 6F.2

Used Bitzer 4H.2 / 6G.2 / 6F.2 freon compressor rack, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, control panel and liquid receiver with a volume of 20 liters.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.







