

Performer SZ 240 A4ABA

Specifications


Marka	Performer
Typ	SZ 240 A4ABA
Czynnik chłodzący	Freon
Refrigerant type	R407 C or other types
kW at +10°C/+40°C	81,8
kW at 0°C/+40°C	55,8
kW at -5°C/+40°C	45,3
kW at -10°C/+40°C	36,4
kW at -20°C/+40°C	22,4
Rozmiary	350x350x360 mm (LxWxH)
Stock	4



Description

Used Performer SZ 240 A4ABA

Used Performer SZ240A4BA Scroll compressor(s/n: QE11 4921176) // 400V 3 ~ 50 Hz





COMPRESSOR MODEL DESIGNATION

Performer® scroll compressors are available both as single compressors and as tandem units. The example below presents single compressor nomenclature.

For tandem assemblies, please refer to the Performer® Parallel Application Guidelines documentation.

Nomenclature

Family, lubricant & refrigerant	Nominal capacity	Voltage	Version	Evolution Index
S Z S Y	1 8 5 3 0 0	S A	4 9	R AA
Family, lubricant & refrigerant SM : Scroll, mineral oil, for R-22 SY : Scroll, POE lubricant, for R-22 SZ : Scroll, POE lubricant, for R-407C - R-134a	Nominal capacity in thousand Btu/h at 60 Hz, R-22, ARI conditions	UL Index	Version	
Motor voltage code: 3: 200-230/3/60 4: 380-400/3/50 - 460/3/60 6: 230/3/50 7: 500/3/50 - 575/3/60 9: 380/3/60				

*For this assembly, please contact Danfoss

Connection details

Model	SM/SZ 084 - 090 - 100 110 - 120 - 148 - 161	SM/SZ 115 - 125 - 160 - 175 - 185	SY/SZ 240 - 300		SY/SZ 380	
Version	V	R	C	MA MB	AA AB	AA AB
Suction and discharge connection	brazed	rotolock	brazed	rotolock	brazed	brazed
Oil sight glass	threaded	threaded	threaded	threaded	threaded	threaded
Oil equalization connection	3/8" flare	3/8" flare	3/8" flare	1/2" flare	1/2" flare	1/2" flare
Oil drain connection	-	1/4" NPT	1/4" NPT	1/4" NPT	1/4" NPT	1/4" NPT
Low pressure gauge port (schraeder)	1/4" flare	1/4" flare	1/4" flare	1/4" flare	1/4" flare	1/4" flare