

Goedhart DVS 61454

Specifications

Marka	Goedhart
Typ	DVS 61454
Ogólna wydajność w kW	9,3
Czynnik chłodzący	Freon
Liczba wentylatorów	1
Średnica wentylatora mm	4
Rozmrażanie	None
Podwójny odpływ	✓
Przepływ powietrza w m ³ /h	4239
Rozmiary	1040x1470x520 mm
Uwagi	Y.o.b. 1997
Remarks	Surface 78 m2
Volume	12,0 dm ³
Waga	99 kg
Stock	10



Description

Used Goedhart DVS 61454

Used Goedhart DVS 61454 double discharge evaporator with a Woods fan. Min. workingtemp. -5°C max. 43°C. *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



DVS 4mm Technical data

Type DVS	3x400V-50Hz-4pole (1500 min ³ /room.)										3x400V-50Hz-6pole (1000 min ³ /room.)										Connections									
	E1000					E1250					E1500					E1750					Refrigerant					Refrigerant				
	E1000					E1250					E1500					E1750					Refrigerant					Refrigerant				
	Power kW	Q _{max} kW	Q _{max} m ³ /h	Q _{max} dB(A)	Q _{max} dB(A)	Power kW	Q _{max} kW	Q _{max} m ³ /h	Q _{max} dB(A)	Q _{max} dB(A)	Power kW	Q _{max} kW	Q _{max} m ³ /h	Q _{max} dB(A)	Q _{max} dB(A)	Power kW	Q _{max} kW	Q _{max} m ³ /h	Q _{max} dB(A)	Q _{max} dB(A)	in	out	in	out	in	out	in	out		
4.1.40.4	4.5	4.9	3682	52	11	1790	41	58	10	120	1056	1180	420	656		15	15	4/19	21/14"											
4.1.45.4	6.5	6.6	2857	52	11	2591	47	52	8	118	1056	1230	520	656		22	12	4/19	21/14"											
4.1.50.4	8.5	7.8	4610	56	13	3291	47	52	8	118	1056	1230	520	656		22	12	4/19	21/14"											
4.1.55.4	10.5	10.2	6286	63	15.4	3991	59	78	12	147	1356	1280	520	956		22	12	4/19	21/14"											
4.1.60.4	12.5	12.4	9904	63	15.7	4215	59	117	18	182	1356	1480	520	956		28	16	4/19	21/14"											
4.1.65.4	14.5	14.4	14021	63	15.7	4215	59	117	18	182	1356	1480	520	956		28	16	4/19	21/14"											
4.1.70.4	16.5	16.4	19054	63	15.7	4215	59	117	18	182	1356	1480	520	956		28	16	4/19	21/14"											
4.1.75.4	18.5	18.3	24981	63	15.7	4215	59	117	18	182	1356	1480	520	956		35	16	4/19	21/14"											
4.1.80.4	20.5	20.3	32071	63	15.7	4215	59	117	18	182	1356	1480	520	956		35	16	4/19	21/14"											

4.1.40.4	4.5	4.9	3682	52	11	1790	41	58	10	120	1056	1180	420	656		15	15	4/19	21/14"										
4.1.45.4	6.5	6.6	2857	52	11	2591	47	52	8	118	1056	1230	520	656		22	12	4/19	21/14"										
4.1.50.4	8.5	7.8	4610	56	13	3291	47	52	8	118	1056	1230	520	656		22	12	4/19	21/14"										
4.1.55.4	10.5	10.2	6286	63	15.4	3991	59	78	12	147	1356	1280	520	956		22	12	4/19	21/14"										
4.1.60.4	12.5	12.4	9904	63	15.7	4215	59	117	18	182	1356	1480	520	956		28	16	4/19	21/14"										
4.1.65.4	14.5	14.4	14021	63	15.7	4215	59	117	18	182	1356	1480	520	956		28	16	4/19	21/14"										
4.1.70.4	16.5	16.4	19054	63	15.7	4215	59	117	18	182	1356	1480	520	956		28	16	4/19	21/14"										
4.1.75.4	18.5	18.3	24981	63	15.7	4215	59	117	18	182	1356	1480	520	956		35	16	4/19	21/14"										
4.1.80.4	20.5	20.3	32071	63	15.7	4215	59	117	18	182	1356	1480	520	956		35	16	4/19	21/14"										