

DWM D2DL3-75X-AWM/D

Specifications

Marka	DWM
Тур	D2DL3-75X-AWM/D
Czynnik chłodzący	Freon
kW at $+10^{\circ}\text{C}/+40^{\circ}\text{C}$	27.29
kW at 0°C/+40°C	18.68
kW at -5°C/+40°C	15.14
kW at -10°C/+40°C	12.05
kW at -20°C/+40°C	7.01
Stock	1



Description

Used DWM D2DL3-75X-AWM/D

Used, DWM D2DL3-75X-AWM/D Semihermetic piston compressor. You can also use this compressor on alternative types of Freon. For all the other specs (if available), see the picture of the manufacturer model plate or the attached pdf file. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment







Model: D2DL-75 X

Cooling capacity [kW]

tc \ te	-25	-20	-15	-10	-5	0	5	10
30	6.24	8.42	10.94	13.84	17.19	21.01	25.38	30.32
35	5.59	7.70	10.14	12.94	16.16	19.85	24.04	28.81
40	4.96	7.01	9.36	12.05	15.14	18.68	22.71	27.29
45	-	6.34	8.60	11.18	14.14	17.53	21.39	25.77
50	-	5.71	7.86	10.33	13.16	16.39	20.08	24.27
55	181	ies :	7.17	9.52	12.20	15.28	18.79	22.78
60	-	2	6.51	8.74	11.28	14.19	17.52	21.32

Power input [kW]

tc \ te	-25	-20	-15	-10	-5	0	5	10
30	2.81	3.14	3.44	3.68	3.86	3.95	3.95	3.85
35	2.90	3.29	3.64	3.95	4.19	4.37	4.45	4.44
40	2.98	3.41	3.82	4.19	4.51	4.76	4.93	5.00
45	-	3.53	3.99	4.42	4.81	5.13	5.38	5.54
50	180	3.64	4.16	4.65	5.09	5.49	5.82	6.06
55	2	23	4.31	4.86	5.37	5.83	6.24	6.57
60	-	-	4.47	5.07	5.64	6.17	6.65	7.06