

DWM DKMP-5X-CAG

Specifications

Marka	DWM
Тур	DKMP-5X-CAG
Czynnik chłodzący	Freon
kW at -20°C/+40°C	1.31
kW at -30°C/+40°C	0.77
kW at -40°C/+40°C	0.37
kW at -45°C/+40°C	0.22
m3 / h	4
Uwagi	Our capacity table is
	based on Manufacturer
	spec. We would like to
	know which refrigerant is
	in your system
Waga kg.	41
Stock	1



Description

Used DWM DKMP-5X-CAG

Used DWM - Copeland DKMP-5X-CAG Semi-hermetic piston compressors. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment





Cooling capacity [kW]

tc \ te	-50	-45	-40	-35	-30	-25	-20
20	0.32	0.48	0.68	0.92	1.21	1.54	1.93
25	0.26	0.41	0.60	0.83	1.10	1.41	1.78
30	0.20	0.35	0.52	0.74	0.99	1.28	1.63
35	-	0.28	0.45	0.64	0.88	1.15	1.47
40	-	0.22	0.37	0.55	0.77	1.02	1.31
45	-	-	0.30	0.46	0.66	0.89	1.16
50	-	-	-	0.37	0.55	0.76	1.00
55	-	-	-	0.29	0.45	0.63	0.85

Power input [kW]

t _c \ t _e	-50	-45	-40	-35	-30	-25	-20
20	0.35	0.40	0.44	0.49	0.53	0.56	0.59
25	0.34	0.39	0.44	0.49	0.54	0.59	0.63
30	0.32	0.38	0.44	0.50	0.55	0.61	0.66
35	180	0.36	0.43	0.49	0.56	0.62	0.68
40	-	0.34	0.41	0.49	0.56	0.64	0.71
45	-	-	0.40	0.48	0.56	0.64	0.73
50	-	-	-	0.46	0.56	0.65	0.74
55	-	-	-	0.44	0.55	0.65	0.75