

DWM DLSGE-401-EWL

Specifications

| Marka | DWM |
|-------------------|---------------------------|
| Тур | DLSGE-401-EWL |
| Czynnik chłodzący | Freon |
| kW at -20°C/+40°C | 7.71 |
| kW at -30°C/+40°C | 4.51 |
| kW at -40°C/+40°C | 2.07 |
| kW at -45°C/+40°C | 1.20 |
| m3 / h | 22.5 |
| Uwagi | Our capacity table is |
| | based on Manufacturer |
| | spec. We would like to |
| | know which refrigerant is |
| | in your system |
| Uwagi | check working conditions |
| | in attached pdf file |
| Waga kg. | 88 |
| Stock | 1 |



Description

Used DWM DLSGE-401-EWL

Used semi-hermetic compressor DWM -Copeland DLSGE-401-EWL. Our capacity table is based on the used type of Freon. You can also use this compressor(s) on alternative types of Freon. For all the other specs (if available), see the picture of the manufacturer model plate or the attached pdf file. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment





| t _c \ t _e | -50 | -45 | -40 | -35 | -30 | -25 | -20 |
|---|-------------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---|
| 25 | 1.14 | 1.94 | 3.02 | 4.36 | 5.92 | 7.67 | 9.59 |
| 30 | 0.94 | 1.68 | 2.69 | 3.96 | 5.44 | 7.12 | 8.96 |
| 35 | 0.77 | 1.43 | 2.37 | 3.56 | 4.97 | 6.57 | 8.33 |
| 40 | 0.61 | 1.20 | 2.07 | 3.18 | 4.51 | 6.03 | 7.71 |
| 45 | 5 m | 15 | 1.78 | 2.81 | 4.06 | 5.50 | 7.09 |
| 50 | = | 1-1 | - | 2.46 | 3.63 | 4.98 | 6.48 |
| 55 | -51 | 850 | - | 2.12 | 3.20 | 4.47 | 5.88 |
| ver input | | | | | | | |
| t _c \ t _e | -50 | -45 | -40 | -35 | -30 | -25 | -20 |
| CONTRACTOR OF THE PARTY | | -45 1.87 | -40 2.22 | -35 2.58 | -30 2.91 | -25 3.21 | |
| t _c \ t _e | -50 | | | | | | 3.44 |
| t _c \ t _e | - 50 1.55 | 1.87 | 2.22 | 2.58 | 2.91 | 3.21 | 3.44 3.65 |
| t _c \ t _e 25 30 | -50 1.55 1.53 | 1.87 | 2.22 | 2.58 2.64 | 2.91 3.02 | 3.21 3.36 | 3.44 3.65 3.84 |
| t _c \ t _e 25 30 35 | -50 1.55 1.53 1.49 | 1.87 1.87 1.86 | 2.22 2.25 2.27 | 2.58 2.64 2.69 | 2.91 3.02 3.11 | 3.21 3.36 3.50 | 3.44 3.65 3.84 4.01 |
| t _c \ t _e 25 30 35 40 | -50 1.55 1.53 1.49 1.44 | 1.87 1.87 1.86 1.83 | 2.22 2.25 2.27 2.27 | 2.58 2.64 2.69 2.73 | 2.91 3.02 3.11 3.19 | 3.21 3.36 3.50 3.62 | -20 3.44 3.65 3.84 4.01 4.16 4.29 |