

## Sabroe SAB 110 LF

### **Specifications**

| Marka                 | Sabroe  |  |  |  |
|-----------------------|---|--|--|--|
| Тур                   | SAB 110 LF  |  |  |  |
| Czynnik chłodzący     | NH 3 / Freon  |  |  |  |
| kW at +10°C/+40°C     | 218   |  |  |  |
| kW at -10°C/+40°C     | 164   |  |  |  |
| m3 / h                | 262/315   |  |  |  |
| Uwagi                 | Our capacity table is   |  |  |  |
|                       | based on Manufacturer   |  |  |  |
|                       | spec. We would like to  |  |  |  |
|                       | know which refrigerant is   |  |  |  |
|                       |   |  |  |  |
|                       | in your system  |  |  |  |
| Uwagi                 | 2950/3550 RPM //  |  |  |  |
| Uwagi                 |   |  |  |  |
| Uwagi                 | 2950/3550 RPM //  |  |  |  |
| Uwagi   <br>Uwagi     | 2950/3550 RPM //<br>capacity is by  |  |  |  |
|                       | 2950/3550 RPM //<br>capacity is by<br>-10°C/+35°C   |  |  |  |
|                       | 2950/3550 RPM // capacity is by -10°C/+35°C serial number 112152RN                                |  |  |  |
| Uwagi                 | 2950/3550 RPM // capacity is by -10°C/+35°C serial number 112152RN // YOB 2007                    |  |  |  |
| Uwagi    <br>Waga kg. | 2950/3550 RPM // capacity is by -10°C/+35°C serial number 112152RN // YOB 2007 600                |  |  |  |
| Uwagi    <br>Waga kg. | 2950/3550 RPM // capacity is by -10°C/+35°C serial number 112152RN // YOB 2007 600 950x600x750 mm |  |  |  |



### **Description**

#### Used Sabroe SAB 110 LF

Used Sabroe SAB 110 LF screw compressor. Weight 600kg, 950x600x750 mm (LxWxH), serial number 112152RN // YOB 2007,2950/3550 RPM // capacity is by -10°C/+35°C

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also perform a new paint job and arrange the logistics.



# Your partner for used commercial and industrial refrigeration equipment









| Model                                   | R717 R                                  |                                | 22                          | R40  | R404A                |                      | With economiser      |                          |                  |
|---|---|--------------------------------|-----------------------------|------|----------------------|----------------------|----------------------|--------------------------|------------------|
|   | High stage<br>-10/+35°C                 | Booster<br>-40/-10°C           | High<br>-10/+35°C           |      | High<br>-10/+35°C    | stage<br>0/+40°C     | R717<br>-40/+35°C    | R22<br>-40/+35°C         | R404/<br>-40/+3! |
| SAB 110 SM                              | 79                                      | NA                             | 76                          | 103  | 79                   | 107                  | 22                   | 28                       | 28               |
| SAB 110 LM                              | 100                                     | NA                             | 97                          | 130  | 99                   | 135                  | 28                   | 35                       | 36               |
| SAB 110 SF                              | 130                                     | NA                             | 124                         | 167  | 128                  | 173                  | 36                   | 45                       | 47               |
| SAB 110 LF                              | 164                                     | NA                             | 156                         | 211  | 161                  | 218                  | 46                   | 57                       | 59               |
|   | Swe                                     | pt volume                      |                             |      | nsions               |                      | /eight ²)            | Sour                     |                  |
|   |   |                                | pm L                        |      | nsions<br>W          | H<br>m               | /eight <sup>2)</sup> | Sour<br>pressure<br>dB(A | level 3)         |
| Model                                   | 2960 rpi<br>m³/h                        | m   3550 r                     | pm L<br>h m                 |      | W<br>m               | Н                    |                      | pressure                 | level 3)         |
| Model<br>SAB 110 SM                     | 2960 rpi<br>m³/h                        | m 3550 r<br>m³/l               | rpm L<br>h m                | 9 (  | w<br>m               | H<br>m               | kg                   | pressure<br>dB(A         | level 3)         |
| Model  SAB 110 SM SAB 110 LM SAB 110 SF | 2960 rpi<br>m³/h                        | m 3550 r<br>m³/l               | rpm L<br>h m<br>3 1.        | 9 (9 | W<br>m<br>0.9        | H<br>m               | <b>kg</b>            | pressure<br>dB(A         | level 3)         |
| Model<br>SAB 110 SM<br>SAB 110 LM       | Swe<br>2960 rpi<br>m³/h<br>1 140<br>175 | m 3550 r<br>m³/l<br>168<br>210 | pm L<br>h m<br>3 1.<br>0 1. | 9 (9 | W<br>m<br>0.9<br>0.9 | H<br>m<br>1.3<br>1.3 | <b>kg</b> 600 600    | pressure<br>dB(A<br>81   | level 3)         |



# Your partner for used commercial and industrial refrigeration equipment

**HOS BV** www.hosbv.com info@hosbv.com (+31) (0)23-5404237