

Searle DKG90-12

Specifications

Marka	Searle
Typ	DKG90-12
Typ produktu	Drycooler
Ogólna wydajność w kW	121,7
Liczba wentylatorów	3
Czynnik chłodzący	Glycol
wentylatory o średnicy Ø	900 mm
Rozmiary	3900x1160x1250 mm
Waga	586 kg
Stock	1



Description

Used Searle DKG90-12

Used Searle DKG90-12 drycooler with 3 fans 50 Hz - 0,31/0,16 kW - 455/350 RPM - diameter 900 mm.

*All components of this used condensor will be tested on good working, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.



Model	DKG90-12	Serial Number	244014		
Medium (Group)	WATER/GLYCOL ⁽²⁾	Date Code	DC		
Max Pressure	10 bar	Receiver Volume	litr		
Coil Volume	-	Net Weight	586 kg		
Safety Device Settings					
MOTOR SUPPLY			TOTAL AMPS/PHASE		
No. Off x Power	Conn-Volt-Phase-Freq	1	2	3	
3 x 310 W	D 400V-3Ph-Hz	7.2			
	S 400V-3Ph-Hz	3.6	3.6	3.6	
DEFROST			TOTAL AMPS/PHASE		
Power	Voltage-Phase	1	2	3	
searle			CE		
Fareham, UK, PO14 1AR			MADE IN THE E.C.		



searle		3~LS100L		I		CE	
Ta90°C		Ins.cl.F S1		IP55		IK08 20kg	
IEC60034-1	V	Hz	min-1	kW	cosΦ	A	
Δ	400	50	455	0.31	0.47	2.10	
λ	400	50	350	0.16	0.68	0.80	
Δ	430	60	540	0.31	0.46	1.80	
λ	430	60	320	0.16	0.65	0.80	
211.310.312.90 PTO							

		dB(A)	kW	m³/s	63	125	250	500	1K	2K	4K	8K	dB(A)
--	--	-------	----	------	----	-----	-----	-----	----	----	----	----	-------

6 Pole

10, 20, 30	1 x 1	88	63.5	5.50	51	56	53	49	48	44	39	38	53
40, 50, 60	1 x 2	91	132.5	11.00	54	59	56	52	51	47	42	41	56
70, 80, 90	1 x 3	93	205.0	16.50	55	61	58	54	53	48	43	43	58
110, 120	1 x 4	94	265.1	22.00	56	62	59	55	54	50	44	44	59
115, 125	2 x 2	94	265.1	22.00	57	63	60	56	55	50	45	45	59
140, 150	1 x 5	95	337.6	27.50	57	63	60	56	55	51	45	45	60
175, 185	2 x 3	95	410.0	33.00	58	64	60	57	56	51	46	46	60
205, 215	2 x 4	96	546.7	44.00	59	65	61	58	57	52	47	47	61
235, 245	2 x 5	97	675.1	55.00	60	66	62	59	58	53	48	48	62
265, 275	2 x 6	98	820.1	66.00	61	66	63	60	59	54	49	49	63

8 Pole

10, 20, 30	1 x 1	83	56.9	4.45	48	50	47	45	44	38	32	22	48
40, 50, 60	1 x 2	86	113.4	8.90	51	53	50	48	47	41	35	25	51
70, 80, 90	1 x 3	88	175.2	13.35	54	55	52	51	49	44	38	28	53
110, 120	1 x 4	89	233.7	17.80	54	56	53	51	50	44	38	28	54
115, 125	2 x 2	89	226.9	17.80	55	56	53	52	50	45	39	29	54
140, 150	1 x 5	90	288.7	22.25	55	57	54	52	51	45	39	29	55
175, 185	2 x 3	90	350.5	26.70	55	57	54	52	51	45	40	30	55
205, 215	2 x 4	91	467.3	35.60	57	58	55	54	52	47	41	31	56
235, 245	2 x 5	92	577.4	44.50	57	59	56	54	53	48	42	32	57
265, 275	2 x 6	93	701.0	53.40	58	60	57	55	54	48	43	33	58

12 Pole

10, 20, 30	1 x 1	75	40.3	2.85	41	42	40	37	36	31	25	14	40
40, 50, 60	1 x 2	78	81.1	5.70	44	45	43	40	39	34	28	17	43
70, 80, 90	1 x 3	80	121.7	8.55	45	47	44	41	41	35	30	19	45