

Güntner GVH 080.2A / 2x6-E(S)

Specifications

Производитель	Güntner
Тип	GVH 080.2A / 2x6-E(S)
Тип продукта	Air Cooled Condenser
кВт	431
К-во вентиляторов	12
Скорость вращения вентиляторов	380/240
Хладагент	Freon
Поток воздуха м³/час	103.200
диаметр вентиляторов Ø	800 mm
поверхность (m2)	2003 m²
Объем трубки	257 dm³
Размеры	11900 x 2300 x 1400 mm (LxWxH)
вес	2066 Kg
Примечания	Y.o.b. 2006
Stock	1



Description

Used Güntner GVH 080.2A / 2x6-E(S)

Used Güntner GVH 080.2A / 2x6 - E(S) air cooled condensor extra silence. Complete with 12 Güntner fans 50 Hz - 0,12/0,03 kW - 380/240 RPM - diameter 800 mm. Mentioned capacity at delta. *All components of this used condensor will be tested on good working, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.





für Temperaturbedingungen
nach Eurovent

Gewichte und Maße

für Temperaturbedingungen
acc. to Eurovent

Weights and Measures

GVH/V ...-E... - 2 reihig - 2 rows														
Typ Type	$\dot{Q}_0$ Nennleistung Nominal capacity		$\dot{V}_v$ Luftvolumenstrom Air volume flow		aufgenommene el. Leistung consumed power P_e total		Energieeffizienzkategorie Energy efficiency class	Schalldruck- pegel Sound pressure level		Strang- Anzahl Number of passes	Gewicht Weight	Rohr- volumen Tube volume	Fläche Surface	
	R404A $\Delta t = 15\text{ K}$													
	Δ	Y	Δ	Y	Δ	Y		Δ / Y	Δ					Y
	kW	kW	m³/h	m³/h	kW	kW		dB(A)10m			kg	l	m²	
080.3A/2x2	141	104	34400	23000	0,9	0,5	A / A	35	25	30	768	91	668	
080.3B/2x2	155	115	36400	24600	0,9	0,5	A / A	35	25	30	874	108	808	
080.3A/2x3	212	156	51600	34500	1,4	0,7	A / A	36	26	45	1055	134	1002	
080.3B/2x3	234	173	54600	36900	1,4	0,7	A / A	36	26	45	1201	159	1212	
080.3A/2x4	286	210	68800	46000	1,9	0,9	A / A	38	28	45	1383	178	1335	
080.3B/2x4	313	232	72800	49200	1,9	0,9	A / A	37	27	45	1583	211	1617	
080.3A/2x5	357	261	86000	57500	2,4	1,2	A / A	38	28	90	1729	218	1669	
080.3B/2x5	393	288	91000	61500	2,4	1,2	A / A	38	28	90	1957	259	2021	
080.3A/2x6	431	316	103200	69000	2,8	1,4	A / A	39	29	90	2066	263	2003	
090.2A/2x2	186	130	50800	30800	2,2	1,1	B / A	43	33	30	794	91	668	
090.2B/2x2	211	150	55600	34800	2,2	1,1	B / A	43	33	30	899	111	808	
090.2A/2x3	283	196	76200	46200	3,3	1,7	B / A	44	34	45	1092	134	1002	
090.2B/2x3	320	227	83400	52200	3,3	1,7	B / A	44	34	45	1239	164	1212	
090.2A/2x4	377	263	101600	61600	4,4	2,2	B / A	46	36	45	1434	178	1335	
090.2B/2x4	427	300	111200	69600	4,4	2,2	B / A	46	36	90	1634	218	1617	
090.2A/2x5	475	328	127000	77000	5,5	2,8	B / A	46	36	90	1752	224	1669	
090.2B/2x5	539	380	139000	87000	5,5	2,8	B / A	46	36	90	2060	265	2021	
090.2A/2x6	574	397	152400	92400	6,6	3,3	B / A	47	37	90	2142	257	2003	