

Sabroe TSMC 108L MK2

Specifications

Бренд	Sabroe
Тип	TSMC 108L MK2
Хладагент	NH 3 (ammonia)
кВт at -10°C/+40°C	257,3
кВт at -20°C/+40°C	174,1
кВт at -30°C/+40°C	109,4
кВт at -40°C/+40°C	64,6
Управление	✓
производительностью	
На стальной раме	✓
Маслоотделитель	✓
m3 / h	415
Размеры	2080x1220x1610 mm (LxWxH)
Stock	1



Description

Used Sabroe TSMC 108L MK2

Used Sabroe TSMC 108L MK2 two-stage reciprocating compressor on a steel frame with 2 oil separators. It is possible to get this compressor unit with an electric motor.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





		AARHUS DENMARK	
OVUR. 32100			
Baujahr	1986	Behälter nr.	66075
Berechnungs norm	AD-MERKBLÄTTER		
Abnahme nr.	124VP29612		
	Mantel seite	Rohr seite	
Medie			
Max. Betriebs- überdruck	25		bar
Probedruck	32,5		bar
Max. Betriebs- temperatur	120		°C
Min. Betriebs- temperatur	20		°C
Inhalt	62		liter