

Bitzer 6G-40.2

Specifications

Тип 6G-40.2 Хладагент Freon kW at 0°C/+40°C 102,6 kW at -5°C/+40°C 85,4 кВт at -10°C/+40°C 70,3 кВт at -20°C/+40°C 46,0 кВт at -30°C/+40°C 28,0 кВт at -40°C/+40°C 14,9 Система
kW at 0°C/+40°C 102,6 kW at -5°C/+40°C 85,4 κΒτ at -10°C/+40°C 70,3 κΒτ at -20°C/+40°C 46,0 κΒτ at -30°C/+40°C 28,0 κΒτ at -40°C/+40°C 14,9
kW at -5°C/+40°C 85,4 κBτ at -10°C/+40°C 70,3 κBτ at -20°C/+40°C 46,0 κBτ at -30°C/+40°C 28,0 κBτ at -40°C/+40°C 14,9
кВт at -10°C/+40°C 70,3 кВт at -20°C/+40°C 46,0 кВт at -30°C/+40°C 28,0 кВт at -40°C/+40°C 14,9
кВт at -20°C/+40°C 46,0 кВт at -30°C/+40°C 28,0 кВт at -40°C/+40°C 14,9
кВт at -30°C/+40°C 28,0 кВт at -40°C/+40°C 14,9
кВт at -40°C/+40°С 14,9
· · ·
Система
СИСТЕМА
маслоуравнивания
Смотровое стекло
m3 / h 126,8
Macca 238
Размеры 870x610x520 mm
(LxWxH)
Stock 1



Description

info@hosbv.com

Used Bitzer 6G-40.2

Used Bitzer 6G-40.2 semi-hermetic reciprocating compressor on Freon with a sight glass. The compressor has a displacement of 126,8 m³/h. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.



Your partner for used commercial and industrial refrigeration equipment







