

Carrier 30 HXC 130

Specifications

Производитель	Carrier
Тип	30 HXC 130
Тип продукта	Water Cooled Chiller
кВт	450,0
Мощность, тонн	128,0
Хладагент	Freon
Тип хладагента	R134a
Масса	2474
Sizes	3800x1000x1850 mm (LxWxH)
Compressor(s) type & model	1 Carlyle 06NA2174S7NC-A00 & 1 Carlyle 06NA2174S7NC-A00
Display	Carrier Pro-Dialog Plus
Примечания	Y.o.b. 2007
Stock	1



Description

Used Carrier 30 HXC 130

Used Carrier 30 HXC 130 water cooled chiller on R134a. Complete with 1x Carlyle 06NA2209S7NC-A00 & 1x Carlyle 06NA2174S7NC-A00 screw compressors, Carrier 09RX2457 shell and tube functioning as condenser with a water volume of 78 dm³, shell and tube functioning as evaporator with a water volume of 65 dm³ and a Carrier Pro-Dialog Plus display.

*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER		12P703120	
2 - MODELE - MODEL MODELLNUMMER		30HXC130-A0321-PEE - -	
3 - VARIANTE VARIANT VARIANTE		30HXC	
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSJAHR UND DATUM		27/02/2007	
5 - FLUIDE - REFRIGERANT KÄLTEMITTEL		R 134 a	
6 - GROUPE - GROUP GRUPPE		2	
7 - CHARGES CIRCUIT A/B REFRIGERANT CHARGE A/B KREISLAUF A/B		51.0 Kg /	47.0 Kg
9 - FLUIDE D'INERTAGE INERTING REFRIGERANT NEUTRALISIERUNG-MEDIUM		23 - AZOTE - NITROGEN - STICKSTOFF	
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULÄSSIGE MIN/MAX - DRUCKE		(PS) -0.9 / 25.0 bar	-0.9 / 25.0 bar
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULÄSSIGE MIN/MAX - TEMPERATUREN		(TS) -20.0 / 80.0 °C	-20.0 / 80.0 °C
12 - PRESSION DE DECLANCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK		21.8 bar	* bar
13 - PRESSION DE DECLANCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSVENTIL - SOLLDRUCK		25.0 bar	25.0 bar
14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE UNIT LEAK TEST PRESSURE LECKTEST-DRUCK DES GERÄTS			15.0 bar
15 - TENSION VOLTAGE SPANNUNG		460 V	10% 10%
17 - FREQUENCE FREQUENCY FREQUENZ		~ 60 Hz	18 - I MAXIMALE MAXIMUM AMPS MAXIMAL STROM
19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME		180.0 / * kW	253.0 / * A
20 - POIDS NET NET WEIGHT NETTOGEWICHT		2474 Kg	
24 - PRESSION DE DECLANCHEMENT DES DISQUES DE RUPTURE RUPTURE DISKS SETTING EINSTELLDRUCK DER BERTSCHEIBEN		* bar	* bar

CE 0062

Carrier

MANUFACTURED IN FRANCE BY
CARRIER SCS - 01120 MONTLUEL - FRANCE
A SUBSIDIARY OF CARRIER CORPORATION
SYRACUSE NEW YORK UNITED STATES OF AMERICA







