

Dorin SCS373-D

Specifications

Бренд	Dorin
Тип	SCS373-D
Хладагент	CO2
Refrigerant type	R744
kW at 0°C/+40°C	56,1*
kW at -5°C/+40°C	48,1*
кВт at -10ºC/+40ºC	41,4*
кВт at -20ºC/+40ºC	29,0*
кВт at -30ºC/+40ºC	19,6*
Электродвигатель	50 Hz - 18,5 kW - 2900
Specs	RPM
Смотровое стекло	✓
Смотровое стекло m3 / h	12,7
m3 / h	12,7
m3 / h	12,7 * Capacities refer to
m3 / h	12,7 * Capacities refer to subcritical operation
m3 / h	12,7 * Capacities refer to subcritical operation conditions and a
m3 / h	12,7 * Capacities refer to subcritical operation conditions and a condensing temperature
m3 / h Примечания	* Capacities refer to subcritical operation conditions and a condensing temperature of 15°C
m3 / h Примечания Масса	* Capacities refer to subcritical operation conditions and a condensing temperature of 15°C 155
m3 / h Примечания Масса	12,7 * Capacities refer to subcritical operation conditions and a condensing temperature of 15°C 155 700x350x450 mm



Description

Used Dorin SCS373-D

New Dorin SCS373-D semi-hermetic reciprocating compressor for CO2. The compressor has a displacement of 12,7 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.















